



ArcticChill 98

Direct Chill Cooler Dispensing Chilled & Ambient Water

- Chiller capacity: 30 - 40 ltrs of below 12°C chilled water/hour
- Copious amounts of ambient water
- Can be fitted with drip tray overflow kits & mains drainage
- Fits our standard cowl and wall bracket
- FloodGuard inlet solenoid protects the cooler against large scale flooding
- Impressive 23cm dispensing height

**The ArcticChill 98
Delivers 30 - 40 ltrs
of Below 12°C Chilled
Water Per Hour &
Copious Amounts Of
Ambient Water**



**23cm Dispensing
Height To Fill
Bottles**

Description	Hourly Output		Temp	Dimensions H X W X D (mm)	Weight (Kg)
	Chilled	Ambient			
POU Floor Standing	30-40 Ltrs/Hr	Indefinite	Below 12C	1135 x 340 x 340	25

AAFIRST
WATER COOLERS
& BOILERS



Quality – Reliability – Integrity



ArcticChill 98

Direct Chill Cooler Dispensing Chilled & Ambient Water



Key Feature

First select ambient or cold, then hold the dispensing button down

Accessories For The ArcticChill 98

Installation rail with filter. Includes compression fitting, 1-Micron green filter, water block, copper pressure reducing valve & non-return valve



FloodGuard - closed inlet solenoid only opens to allow water into the cooler, when water is dispensed. By remaining closed all other times it protects the cooler against leaks



Filter housing with carbon block candle & nanofilter



Mains drainage - connect the drip tray to mains drainage. Can be supplied with a pump, to pump the water over 50m & a rise of 5m



Cowling to fix the cooler securely to the wall. (Supplied separately)



10 litre overflow system with alarm to signal when full. (Factory fitted)



3 Litre overflow kit connects the drip tray to a 3 litre alarmed overflow container. The container has a tap to empty without removing it



A pumped main drainage system pumps the waste water from the drip tray over a distance of 100m & a rise of 5m. (Factory installed)

